

Air air heat exchangers

[HOME](#) > [CATEGORIES](#) > [AIR CONDITIONING CONTROL CABINETS](#) > [AIR- AIR HEAT EXCHANGERS](#)

Heat exchangers with cross and counter-current flows designed for indoor and outdoor applications. High quality vacuum soldering technology Seifert allows for the best in class heat dissipation and a brand recognized in its sectors that offers compact solutions.

The exchangers satisfy the NEMA and IP standards. Air-air heat exchangers are designed in order to satisfy all telecommunication requirements. Our clients can also choose the best protection against corrosion and achromatic surfaces. The operation is very simple. Core of the exchanger transfers heat from the internal circuit to ambient circuit through aluminium surface, therefore there is no direct contact or air mixing between external and internal air.

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



No.	Model - performance	Voltage / frequency	Dimensions [mm] (width x height depth)	montage	Temperature and action range	Catalogue No
1	LT 5025 - 25 W/K	230 V - 50/60 Hz	360 x 545 x 140	External	-5°C - +55°C	5.502500011
2	LT 5060 - 60 W/K	230 V - 50/60 Hz	395 x 1740 x 180	External	-5°C - +55°C	5.506000011
3	LT 5070 - 70 W/K	48 V DC	465 x 1010 x 150	Internal	-5°C - +55°C	5.5070048
4	LT 5080 - 70 W/K	230 V - 50/60 Hz	465 x 1010 x 150	Internal	-5°C - +55°C	5.50800001
5	LT 5095 - 95 W/K	48 V DC	450 x 1150 x 150	Internal	-5°C - +55°C	5.5095048

