

BRASS PLUGS EX

HOME > CATEGORIES > SOCKETS AND PLUGS EX > ATEX ZONE > BRASS PLUGS EX

The 2P-PE brass cable-mounted plugs are designed for use in hazardous areas. Thanks to their robust construction and high quality materials, they ensure reliability and safety in demanding industrial environments. The product is ATEX and IECEx certified, guaranteeing compliance with international safety standards. These connectors are ideal for use in chemical, petrochemical, gas and other environments where there is a risk of explosion.

TECHNICAL DATA

- **Marking:** II 2 G Ex de IIC T6...T5 Gb, II 2 D Ex tb IIIC T65°C Db
- **Certificates:** TÜV 14 ATEX 7565X, IECEx TUR 15.0018X
- **Zones of application:** Zone 1 (gas hazard), zone 21 (dust hazard)
- **Degree of protection:** IP56
- **Operating temperature range:** -40°C to +40°C
- **Contact configuration:** 2P-PE (two poles + earth)
- **Rated current:** 16A
- **Housing material:** Brass

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



BRASS PLUGS EX

No.	Type	Connection thread	Voltage	Catalogue number
1	Ex-5516/ST/6h/1x24-Z14	M 24 x 1,5	250 V	10030777
2	Ex-5516/ST/6h/1x24-W08	M 24 x 1,5	250 V	10030750
3	Ex-5516/ST/4h/1x24-Z14	M 24 x 1,5	130 V	10101756

