

Cable gland Ex

HOME > CATEGORIES > CABLE GLANDS EX > CABLE GLAND EX

Explosion-proof socket gland.

TECHNICAL DATA:

- Marking according to 94/9/EC (ATEX) II 2G Ex e II / II 2D Ex tD A21 IP66
- EC type examination certificate PTB 00 ATEX 3121
- IECEx Certificate of Conformity IECEx BKI 08.0007
- Marking according to IECEx Ex e II / Ex tD A21 IP66 T85°C
- Permissible ambient temperature -40°C to +85°C / -50°C to +80°C (optional)
- Protection level according to EN 60529 IP66
- Material Polyamide

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



DATA SHEET

No. Thread **Cable Ø mm** **Catalogue no.**

1	M20 x 1,5	8-13	5.GHG 960 1949 R0111
2	M25 x 1,5	11-16	5.GHG 960 1949 R0112
3	M32 x 1,5	15-20	5.GHG 960 1949 R0113
4	M40 x 1,5	19-27	5.GHG 960 1949 R0114
5	M50 x 1,5	26-34	5.GHG 960 1949 R0115
6	M63 x 1,5	35-46	5.GHG 960 1949 R0116

