



# **Groesteen, Luksemburg**

HOME > CATEGORIES > COMPLETED PROJECTS > GROESTEEN, LUKSEMBURG

120MVA power transformer control cabinet. The switchgear is a continuation of many years of cooperation with our client. This is already the 10th implementation of the wind farm project in Luxembourg.

Supply voltage: 400/230V AC Control voltage: 220V DC Rated current: 40A Tightness class: IP66 Corrosion protection: C4 Operating temperature range: -20°C to 40°C

## **IMPLEMENTATION DATE: FEBRUARY 2020**

# Switchboard:

Custom made wardrobe at the customer's request.

Dimensions:1400mm x 2000mm x 600mm

**Type:**SZS-OH – hanging housing, with the possibility of mounting on the transformer support frame using pins in the rear part of the housing. Made of stainless steel, polished coating.

Color:RAL7038

Manufacturer:Radiolex

SO-G-13055-A01 - SZS-OH-1400\*2000\*600 - switchboard housing - manufacturer Radiolex

### ABB equipment used:

1SBH137001R1322 - NF22E-13 - Contactor 2NO/2NC 6 A 230 V AC/DC

```
1SBL183001R8810 -AL 16-30-10 - Contactor 220V DC
```

1SVR405611R9100 - CR-M220DC2L - 220V DC relay

1SVR405651R1000 -CR-M2SS- Relay socket mounted on a DIN rail 7A 250V

1SVR730010R0200 -CT-MFS.21S- Timer relay 24-240V AC/DC; Time range: 0.05s - 300h

1SVR730794R3300 - CM-PVS.41S - 3ph relay 300-500V AC

2CCA703050R0001 - E218-16-11 - Modular switch 16A 250VAC

#### **Apator equipment used:**

- 4G10-207-U 4G10-207-U Reversing cam switch 1-2 1P 10A
- 63-840306-031 4G25-10-PK Cam switch 0-1 3P 25A
- 63-840343-011 -4G10-53-U Cam switch 1-0-2 3P 10A
- 63-840398-051 4G63-92-PK Cam switch 0-1 3P 63A

## **Stego equipment used:**

- 01140.0-00 **KTO-011** Thermostat 1NC, 0 to +60°C
- 02527.0-00 SL025 Slimline SL series lamp 230V 11W
- 08400.0-03 DA084 Pressure equalizing cartridge
- 08410.0-00 **DD084** Drying element
- 14007.0-00 HG140 Semiconductor heater AC/DC 110-250V, 100W

## Apparatus from other manufacturers used:

10387303 -TC20CV- current transformers 10A manufactured by Triquest

2967060 – **PLC-RSC-24DC/21-21** – Universal relay of the PLC series 24V DC 6A manufactured by PhoenixContact

5102-DNPM-MCM3 - DNP 3.0 protocol driver, ProLinx manufacturer ProSoftTechnology

doublePRIME IDD -IDD- Monitor of outflow parameters manufactured by doble

Mtec-EPT202 - MteC-EPT202 - Transformer protection controller manufactured by Messko

P32100P0 - PT100/4-20mA - Temperature control relay manufactured by Knick

RMA42-AA-C -RMA42- Measurement signal transducer manufactured by Endress+Hauser

T/Guard 408 - Qualitrol T/Guard 408 - Fiber optic temperature controller manufactured by Qualitrol

Tapcon 260 -**Tapcon 260 -**Tap changer controller manufactured by Maschinenfabrik Reinhausen

# GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI

