

## Screw plugs made of plastic Ex

HOME > CATEGORIES > CABLE GLANDS EX > SCREW PLUGS MADE OF PLASTIC EX

The explosion-proof plastic plug will find use wherever a conduit hole is left unused.

### BASIC DATA:

- Wide range of sizes
- Hand tightening - just a little torque
- IP66/IP68 protection
- International approvals

### TECHNICAL DATA:

- Marking according to 94/9/EC (ATEX) II 2G Ex e II / II 2D Ex tD A21 IP66
- EC type examination certificate M20-M50: PTB 98 ATEX 3130 / M63: PTB 03 ATEX 1058 (II 2 G only)
- IECEx Certificate of Conformity IECEx PTB 03.0000 (M20 - M50)
- Marking according to IECEx Ex e II
- Permissible ambient temperature M20-M50: -55°C to +55°C / M63: -20°C to +55°C
- Protection level according to EN 60529 IP66 / IP68: 1 m depth (in water) for 0.5 h
- Material Polyamide

### GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI





## Screw plug

**No. Thread Catalogue no.**

1	M16 x 1,5	5.GHG 960 1952 R0111
2	M20 x 1,5	5.GHG 960 1952 R0112
3	M25 x 1,5	5.GHG 960 1952 R0113
4	M32 x 1,5	5.GHG 960 1952 R0114
5	M40 x 1,5	5.GHG 960 1952 R0115
6	M50 x 1,5	5.GHG 960 1952 R0116
7	M63 x 1,5	5.GHG 960 1952 R0117

