

SoliTherm ComPact

[HOME](#) > [CATEGORIES](#) > [AIR CONDITIONING CONTROL CABINETS](#) > [SOLITHERM COMPACT](#)

Reliability and user friendliness are the best ways to describe the electronic controller being used in the ComPact air conditioners. The display indicates temperature and operating status and can be easily set and adjusted by the user via a Touch Pad.

A complete model range from 320 W up to 4 kW with simple operation were the key ideas during the development. NWe have also placed a strong emphasis in standardising components, versions and sizes thus diminishing the need of large spare part stocks, complex training or long unit selection processes.

All ComPact units have powder coated, steel enclosures (RAL 7035). For applications where hygiene and corrosion protection are required, we offer a stainless steel cover for all ComPact models. Units with a cooling capacity of 2 kW and above can be optionally supplied with an electric condensate evaporator.

For a universal use of our ComPact units we also offer models for recessed mounting. The available recessed depth (A) varies from 30 to 120 mm. The part numbers xxxxxx81 have a standard depth of 90 mm. Please contact us for others models and part numbers.

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



No.	Type - Cooling capacity L35L35 / L35L50 (DIN 3168)	Voltage / Frequency	Dimensions (W × H × D mm)	Catalogue No.
1	KG 4304 - 320 W / 200 W	230 V - 50/60 Hz	280 × 500 × 200	5.43040001
2	KG 4304 - 320 W / 240 W	120 V - 60 Hz	280 × 500 × 270	5.43041001
3	KG 4304 - 320 W / 240 W	400/460 V - 50/60 Hz 2~	280 × 500 × 270	5.43042001
4	KG 4305 - 550 W / 410 W	230 V - 50/60 Hz	315 × 650 × 260	5.43050001
5	KG 4305 - 550 W / 410 W	120 V - 60 Hz	315 × 650 × 260	5.43051001
6	KG 4305 - 550 W / 410 W	400/460 V - 50/60 Hz 2~	315 × 650 × 260	5.43052001
7	KG 4308 - 750 W / 470 W	230 V - 50/60 Hz	315 × 650 × 260	5.43080001
8	KG 4308 - 750 W / 480 W	120 V - 60 Hz	315 × 650 × 260	5.43081001
9	KG 4308 - 750 W / 480 W	400/460 V - 50/60 Hz 2~	315 × 650 × 260	5.43082001
10	KG 4309 - 850 W / 610 W	230 V - 50/60 Hz	315 × 650 × 260	5.43090001
11	KG 4309 - 850 W / 600 W	120 V - 60 Hz	315 × 650 × 260	5.43091001
12	KG 4309 - 850 W / 600 W	400/460 V - 50/60 Hz 2~	315 × 650 × 260	5.43092001
13	KG 4310 - 1 kW / 660 W	230 V - 50/60 Hz	315 × 650 × 260	5.43100001
14	KG 4310 - 1 kW / 660 W	120 V - 60 Hz	315 × 650 × 260	5.43101001
15	KG 4310 - 1 kW / 720 W	400/460 V - 50/60 Hz 2~	315 × 650 × 260	5.43102001
16	KG 4315 - 1,50 kW / 1,22 kW	230 V - 50/60 Hz	395 × 980 × 260	5.43150001
17	KG 4315 - 1,50 kW / 1,22 kW	120 V - 60 Hz	395 × 980 × 260	5.43151001
18	KG 4315 - 1,50 kW / 1,22 kW	400/460 V - 50/60 Hz 2~	395 × 980 × 260	5.43152001
19	KG 4320 - 2 kW / 1,6 kW	230 V - 50/60 Hz	395 × 980 × 260	5.43200001
20	KG 4320 - 2 kW / 1,6 kW	120 V - 60 Hz	395 × 980 × 260	5.43201001
21	KG 4320 - 2 kW / 1,63 kW	400/460 V - 50/60 Hz 3~	395 × 980 × 260	5.43202001
22	KG 4325 - 2,5 kW / 1,97 kW	230 V - 50/60 Hz	500 × 1230 × 340	5.43250001
23	KG 4325 - 2,5 kW / 1,97 kW	120 V - 60 Hz	500 × 1230 × 340	5.43251001
24	KG 4325 - 2,5 kW / 1,97 kW	400/460 V - 50/60 Hz 2~	500 × 1230 × 340	5.43252001
25	KG 4330 - 3 kW / 2,38 kW	230 V - 50/60 Hz	500 × 1230 × 340	5.43300001
26	KG 4330 - 3 kW / 2,42 kW	120 V - 50/60 Hz	500 × 1230 × 340	5.43301001
27	KG 4330 - 3 kW / 2,39 kW	400/460 V - 50/60 Hz 3~	500 × 1230 × 340	5.43302001
28	KG 4340 - 4 kW / 3,18 kW	230 V - 50/60 Hz	500 × 1230 × 340	5.43400001
29	KG 4340 - 4 kW / 3,18 kW	400/460 V - 50/60 Hz 3~	500 × 1230 × 340	5.43402001

