

SoliTherm PROTEC Outdoor

[HOME](#) > [CATEGORIES](#) > [AIR CONDITIONING CONTROL CABINETS](#) > [SOLITHERM PROTEC OUTDOOR](#)

SOLITHERM PROTEC enclosure air conditioners are designed for use in extremely harsh environments such as the petrochemical industry, water treatment plants, port areas and extreme weather conditions. The coated condenser and coated inner tubes on the ambient side, as well as the stainless steel housing made of V4A (AISI 316), provide increased protection against chemicals and salt spray.

Protection ratings of IP 56, NEMA / Type 12, 3R, 4X ensure that your electronics are always maintained at the required temperature in any corrosive environment.

AN EFFECTIVE SOLUTION FOR OUTDOOR USE

- AISI 316 (V4A) stainless steel housing
- high degree of protection IP 56, NEMA / UL Type 3R/4X
- IP 66 condensate evaporation
- integrated heater
- coated condenser
- coated copper pipes
- increased resistance to chemicals and salt mist
- RS 485 MODBUS interface included

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



DOCUMENTS



Seifert complaint - customer form [Kliknij aby pobrać](#)

| No. | Model - cooling power L35L35 (DIN 3168) | Heater | Voltage / Frequency | Dimensions (W x H x D, mm) | Catalogue no. |
|-----|--|--------|---------------------|-------------------------------|---------------|
| 1 | OC 8706 - 600 W | 150 W | 230 V - 50/60 Hz | 250 x 380 x 250 | 5.87060584 |
| 2 | OC 8712 - 1,12 kW | 400 W | 230 V - 50/60 Hz | 305 x 585 x 305 | 5.87120584 |
| 3 | OC 8720 - 2,0 kW | 1000 W | 230 V - 50/60 Hz | 395 x 895 x 305 | 5.87200584 |
| 4 | OC 8740 - 3,9 kW | 2000 W | 400-460 V 60 Hz 3~ | 455 x 1040 x 370 | 5.87402584 |
| 5 | OC 8762 - 6,0 kW | 2000 W | 400-460 V 60 Hz 3~ | 455 x 1135 x 390 | 5.87622584 |

