

SWRS IP 20 - Station switchgear enclosure

HOME > CATEGORIES > STEERING CABINETS > SWRS IP 20 - STATION SWITCHGEAR ENCLOSURE

SWRS – is a standing enclosure, intended for installation of electrotechnical equipment in the form of busbar insulators also contact bays. The standard offer includes versions from 8 to 14 bays.

Type	Corrosivity category	Material / additional description	Coating
SWRS	C3	galvanized steel sheet	RAL7035

GENERAL INFORMATION:

- Ingress protection according to IP code: 20 (door)
- Impact resistance according to IK code: 10
- Operating temperature range: –40 – +80°C

BASIC DATA:

- Body: monobloc type, riveted, with the possibility of serial connection
- Closure: hinged door · Cable entry: open bottom
- Grounding: threaded grounding studs in the door and enclosure body
- Other information: current circuit extension with current cover, 300 mm high
- Internal equipment: in contact bay – perforated angle bars (with the option of installing break switches from leading manufacturers); in extension bays – angle bars with mounting plates
- Enclosure series: Depending on the configuration, the enclosure can consist of a contact bay without extension, contact bay with current circuit extension and current cover or measurement system extension

ADDITIONAL OPTIONS:

- Unusual dimensions
- Painting to any color according to the RAL palette

GALERIA PRODUKTU WRAZ Z PRZYKŁADOWYMI REALIZACJAMI



DOCUMENTS

 [CATALOGUE CARD](#) Kliknij aby pobrać

 [Declaration of compliance for Radiolex products](#) Kliknij aby pobrać

 [Powder coatings maintenance instructions](#) Kliknij aby pobrać

The following table presents enclosures according to the description.

No.	Description - Dimensions (W × H × D mm)	Catalogue No.
1	Contact bay without extension - 860 × 1250 × 400	360-001
2	Contact bay with current circuit extension and current cover - 860 × 2200 × 400	360-002
3	Contact bay with measurement system extension and current circuit extension with current cover - 860 × 2200 × 400	360-003
4	Contact bay without extension - 1060 × 1250 × 400	360-004
5	Contact bay with current circuit extension and current cover - 1060 × 2200 × 400	360-005
6	Contact bay with measurement system extension and current circuit extension with current cover - 1060 × 2200 × 400	360-006
7	Contact bay without extension - 1260 × 1250 × 400	360-007
8	Contact bay with current circuit extension and current cover - 1260 × 2200 × 400	360-008
9	Contact bay with measurement system extension and current circuit extension with current cover - 1260 × 2200 × 400	360-009
10	Contact bay without extension - 1460 × 1250 × 400	360-010
11	Contact bay with current circuit extension and current cover - 1460 × 2200 × 400	360-011
12	Contact bay with measurement system extension and current circuit extension with current cover - 1460 × 2200 × 400	360-012

