

Outdoor Air Conditioner OC 5725-400V



Product Description

Brand name:	SoliTherm ComPact Outdoor
Order Number:	572520001
Colour:	RAL 7035
Protection category IP (IEC 60 529):	IP 56 (NEMA 12, 3 ,3R, 4)
Approvals:	CE
Customs tariff number:	84158200
Material housing:	Mild steel, powder coated

Technical data OC 5725-400V

Cooling capacity / output L35L35:	2.5 kW
Cooling capacity / output L35L50:	1,97 kW
Heating capacity:	1,500 W (optional)
Compressor:	Reciprocating compressor
Refrigerant:	R134a
Refrigerant charge:	480 g
Operating temperature range:	-20°C - +55°C
Max. air volume flow:	Ambient air circuit: 655 m ³ /h Cabinet air circuit: 400 m ³ /h
Mounting:	External
Dimensions (H x W x D):	1,550 x 495 x 355 mm
Weight:	75 kg
Rated operating voltage / frequency:	400/460 V - 50/60 Hz 2~
Rated current L35L35:	2.9 A @ 400 V - 50/60 Hz 2.6 A @ 460 V - 60 Hz
Starting current:	6.1 A @ 400 V 6.8 A @ 460 V
Max. current:	3.6 A @ 400 V 3.2 A @ 460 V
Power consumption L35L35:	940 W @ 400/460 V - 50 Hz 1.18 kW @ 400/460 V - 60 Hz
Fuse rating:	2 x 6 A (T)
Connection:	Connection terminal block

Click the graphics to download the originals.


More CAD graphics can be found on our [Products Downloads page](#).

> [Overview product group Cooling units - Outdoor](#)


Performance Graph:

T = Ambient temperatur

P = Cooling capacity



click image to enlarge

Cutout diagram:


click image to enlarge

[Datasheet](#) created 22.07.2015 (12:18:36). Technical rights reserved.