



Cabinet cooling unit KG 8503-230V



Product Features

Brand Name:	SlimLine Pro	
Order Number:	850300001	
Color:	RAL 7035	
Housing Material:	Mild steel, powder coated	
Ingress protection:	IP 56 / Type 12, 3, 3R, 4	
Note:	pat. D815,265	
Optional:	With 125 W cabinet heater order no. 850301001	
Approvals:	CE, RoHS	
Accessories:	Aluminum filter	
	Cold air outlet duct	
Taric Code:	84158200	

Technical data KG 8503-230V

Cooling capacity L35L35:	350 W @ 50 Hz
	350 W @ 60 Hz
Cooling capacity L35L50:	200 W @ 50 Hz
	215 W @ 60 Hz
Compressor:	Rotary Piston
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	100 g / 3.53 oz.
High / low pressure:	25 / 6 bar
	363 / 87 psi
Temperature range:	10°C - +60°C
Air volume flow (system / unimpeded):	Ambient air circuit: 200 / 408 m ³ /h
	Cabinet air circuit: 122 / 180 m ³ /h
Mounting:	External / recessed
Dimension H x W x D:	600 x 250 x 110 (135) mm
Weight:	14 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
Current L35L35:	1.5 A @ 50 Hz
	1.3 A @ 60 Hz
Starting current:	4 A
Max. current:	1.6 A
Nominal power L35L35:	300 W @ 50 Hz
	300 W @ 60 Hz
Max. power:	355 W
Fuse:	2.8 A (T)
Connection:	5 pole terminal for signals
	4 pole terminal for power

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview product group Cabinet cooling units - SlimLine Pro](#)

